

# Spectrum TrafficLine One Pack Epoxy Paint Grass Green



## SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) 453/2010

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Name** Spectrum TrafficLine One Pack Epoxy Paint Grass Green  
**Product Inclusion** This document covers Spectrum TrafficLine One Pack Epoxy Paint Grass Green only.

#### 1.2. Relevant identified uses of the substance of mixture and uses advised against

**Identified Uses** See technical data sheet. For professional use only.  
**Uses advised against** No specific uses advised against are identified.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Meon Ltd.  
Railside  
Northharbour Spur  
Portsmouth  
PO6 3TU  
+44 (0) 23 9220 0606  
+44 (0) 23 9220 0707  
mail@meonuk.com

#### 1.4. Emergency Telephone Number

**Emergency telephone** +44 (0) 808 118 1922

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

Flam. Liq. 2 - H225, Skin Irrit. 2 - H315, STOT, SE. 3 - H336, Carc. 1B - H360Df, Rep. Tox. 2 - H361d, STOT, RE. 2 - H373 and Chron. Aqua. Tox. 2 - H411.

#### Environmental hazards

Not classified

#### 2.2. Label Elements

Hazard pictograms



**Signal word** Danger  
**Named Chemicals on Label**  
**Contains**

## Spectrum TrafficLine One Pack Epoxy Paint Grass Green

<b>H-statement(s)</b>	H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H350 May cause cancer. H360Df May damage the unborn child. Suspected of damaging fertility. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
<b>P-statement(s)</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe dust, fume, gas, mist, vapours or spray. P280 Wear protective gloves, protective clothing, eye protection and face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313 IF exposed or concerned: Get medical advice or attention. P403+P235 Store in a well-ventilated place. Keep cool.EUH208 Contains 2-butanone oxime. May produce an allergic reaction.
<b>Supplemental hazard information</b>	EUH208 Contains 2-butanone oxime. May produce an allergic reaction. EUH201 Contains lead. Should not be used on surfaces liable to be chewed or sucked by children.

### 2.3. Other hazards

#### Results of PBT and vPvB assessment:

PBT and vPvB not applicable.

### SECTION 3: Composition/information on ingredients

#### SUBSTANCE [ ] MIXTURE [X]

#### Description of mixture

Mixture of resins, solvents, pigments and additives.

#### Dangerous component(s)

Ingredient	Cas-No: EC No: Reach No:	R-Phrases	Concentration
		CLP Hazard Statements	
Toluene	108-88-3 203-625-9 -		10.0-25.0%
		H225, H304, H315, H336, H361d, H373	
Xylene	1300-20-7 215-535-7 -		2.5-10.0%
		H226, H312, H315, H332	
Styrene	100-42-5 202-851-5 -		0.1-1.0%
		H226, H315, H319, H332, H361d, H372	
2-butanone oxime	96-29-7 202-496-6 01-2119539477-28		0.1-1.0%
		H311, H317, H318, H351	
Lead sulfochromate	1344-37-212656-85-8 215-693-7235-759-9		0.5-20.0%
		H350, H360Df, H373, H400, H410	

**Additional Information:** The text for CLP Hazard Statements shown above (if any) is given in Section 16.

### SECTION 4: First aid measures

Show this safety data sheet to the doctor in attendance.

#### 4.1. Description of first aid measures

## Spectrum TrafficLine One Pack Epoxy Paint Grass Green

<b>General notes</b>	In case of doubt, or symptom persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.
<b>In case of inhalation:</b>	Move the exposed person to fresh air at once. Keep person warm and at rest. If breathing is irregular or stopped, administer artificial respiration.
<b>In case of skin contact:</b>	Remove contaminated clothing immediately and wash skin with soap and water. Do not use solvents or thinners.
<b>In case of eye contact:</b>	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
<b>In case of ingestion:</b>	If accidentally swallowed rinse mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do not induce vomiting.
<b>Self-protection of the first aider:</b>	None.

### **4.2. Most important symptoms and effects, both acute and delayed**

None

### **4.3. Indication of any immediate medical attention and special treatment needed**

**Notes to Physician:** None.

**Specific treatment:** None.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable extinguishing media** Alcohol-resistant foam, CO<sub>2</sub>, powders, water spray/mist.  
**Extinguishing media which must not be used for safety reasons** Water jet.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazard** Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

### **5.3. Advice for firefighters**

**Protective actions during firefighting.** Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or watercourses.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours.

### **6.2. Environmental precautions**

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent – avoid use of solvents.

### **6.4. Reference to other sections**

None.

## **SECTION 7: Handling and storage**

### **7.1. Precautions on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been included. Electrical equipment should be protected to the appropriate standard.

Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

## Spectrum TrafficLine One Pack Epoxy Paint Grass Green

Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame, no sparking tools should be used, avoid skin and eye contact, avoid the inhalation of dust, particulates and spray mist arising from the application of this mixture and avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area, for personal protection see Section 8, never use pressure to empty: container is not a pressure vessel, always keep in containers of same material as the original one, comply with the health and safety at work laws and do not allow to enter drains or watercourses.

### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage areas and containers

Store in accordance with the Dangerous Substances and Explosive Atmospheres Regulations, 2002, (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR.

#### Notes on joint storage

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Additional information on storage conditions

Observe label precautions. Store between 5 °C and 25°C in a dry well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. The principles contained in the HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances, should be observed when storing this product.

### 7.3. Specific end uses

No specific advice for end use available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Ingredients with Occupational Exposure Limits (UK WELS)

Name	LTEL ppm	STEL ppm	STEL mg/m <sup>3</sup>	LTEL mg/m <sup>3</sup>	Notes
Toluene	50	100	384	191	Sk
Xylene	50	100	441	220	Sk, BMGV
Styrene	100	250	1080	430	

### 8.2. Exposure controls

#### Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

#### Eye/face protection

Use safety eyewear designed to protect against splash of liquids.

#### Hand protection

For prolonged or repeated handling, use Polyvinyl Alcohol (PVA) OR Viton Rubber (FluorRuber). Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

#### Other skin and body protection

Personnel should wear anti-static clothing made of natural fibre or high temperature resistant synthetic fibre.

#### Environmental exposure controls

Do not allow to enter drains or watercourses.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance: Viscous Liquid

Colour: Various

## Spectrum TrafficLine One Pack Epoxy Paint Grass Green

<b>Odour:</b>	Aromatic hydrocarbons.
<b>Melting point/freezing point:</b>	>-39.3°C
<b>Initial boiling point and boiling range</b>	110-140°C
<b>Flash point:</b>	4°C
<b>Vapour pressure:</b>	>0.3 kPa
<b>Vapour density(air=1):</b>	Heavier than air.
<b>Relative density(g/ml):</b>	1.44-1.52
<b>Solubility:</b>	Miscible with organic solvents.
<b>Partition coefficient:</b>	2.65-3.20 log Pow
<b>Auto ignition temperature:</b>	>480°C
<b>Viscosity:</b>	2.6-2.8 poise.
<b>Explosive properties:</b>	May form explosives mixture with air.

### 9.2. Other information

None.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No reactivity hazards known under normal storage and use conditions.

### 10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition product.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

Carbon monoxide and dioxide, smoke, oxides of nitrogen.

## **SECTION 11: Toxicological information**

No data available.

The mixture has been assessed following the conventional method of the Classification, Labelling and Packaging of Substances and Mixtures Regulation (EC) No. 1272/2008, (CLP) and classified for toxicological hazards accordingly.

### 11.1. Information on toxicological effects

<b>Repeated and prolonged contact with mixture</b>	Cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.
<b>Liquid splashed into eyes:</b>	Cause irritation and reversible damage.
<b>Ingestion:</b>	May cause nausea, diarrhoea and vomiting.
<b>Exposure to component solvents vapour concentration in excess of stated occupational limit:</b>	May result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.
<b>Symptoms and signs:</b>	Include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

No information.

### 12.2. Persistence and degradability

No information.

### 12.3. Bioaccumulative potential

Not available.

### 12.4. Mobility in soil

No information.

### 12.5. Results of PBT and vPvB assessment

Not available.

### 12.6. Other adverse effects

## Spectrum TrafficLine One Pack Epoxy Paint Grass Green

No information.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### European List of Waste classification

Waste code: Name of Waste (according to Commission Decision 2000/532/EC):

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

### SECTION 14: Transport information



<b>14.1 UN number:</b>	1263
<b>14.2 UN proper shipping name</b>	PAINT
<b>14.3 Transport hazard class(es)</b>	3
<b>14.4 Packing group</b>	II
<b>14.5 Environmental hazards</b>	No
<b>14.6 Special precautions for user</b>	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
ADR Tunnel Restriction Code	(D/E)
IMDG EmS	F-E, S-E
IMDG Stowage Category	B
<b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code</b>	Not available

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The information in this Safety Data Sheet is required pursuant to:

Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No. 1907/2006, (REACH).

Classification, Labelling and Packaging of substances and mixtures, Regulation (EC) No. 1272/2008, (CLP).

The Dangerous Substances and Explosive Atmosphere Regulations, 2002, (DSEAR).

The Control of Substances Hazardous to Health Regulations, 2002, (COSHH).

The Health and Safety at work etc Act, 1974, (HSWA)

**Approved codes of Practice and Guidance notes relevant to this Safety Data Sheet:**

## Spectrum TrafficLine One Pack Epoxy Paint Grass Green

The European Chemicals Agency (ECHA) Guidance on the compilation of safety data sheets, Version 2.1.

CEPE Guideline for Safety Data Sheets, 9th Edition.

HSE Approved Code of Practice and Guidance, Dangerous Substances and Explosive Atmospheres.

HSE guidance note, Chemical Warehousing: The Storage of Packaged Dangerous Substances.

HSE publication, EH40/2005 Workplace exposure limits.

### **15.2 Chemical safety assessment**

No chemical safety assessment has been carried out for this mixture by the supplier.

---

### **SECTION 16: Other information**

---

#### **Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

H225 : Highly flammable liquid and vapour.

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H311 : Toxic in contact with skin.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H336 : May cause drowsiness or dizziness.

H351 : Suspected of causing cancer.

H361d : Suspected of damaging the unborn child.

H372 : Causes damage to organs through prolonged or repeated exposure.

H373 : May cause damage to organs through prolonged or repeated exposure.

H350 : May cause cancer.

H360Df : May damage the unborn child. Suspected of damaging fertility.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

EUH201 : Contains lead. Should not be used on surfaces liable to be chewed or sucked by Children

#### **List of Wastes" Acronym & Abbreviation Key:**

BMGV Biological Monitoring Guidance Values are given in Table 2 of EH40/2005 Workplace exposure limits.

Sk Can be absorbed through the skin. Dermal absorption may lead to systemic toxicity.

CLP Classification, Labelling & Packaging Regulation

EC European Commission

EU European Union

US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit

STEL Short term exposure limit

OEL Occupational exposure limit

ppm Parts per million

mg/m<sup>3</sup> Milligrams per cubic meter

TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits

VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable

LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

## **Spectrum TrafficLine One Pack Epoxy Paint Grass Green**

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road

RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code

IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978

IBC International Bulk Container

This information is provided in accordance with the current status of our knowledge and experience. The Safety Data Sheet describes products with a view to relevant safety requirements. This information does not constitute a warranty of properties, features or qualities.